

HoistQuip
 Cartmel Drive
 Harlescott Industrial Estate
 Shrewsbury
 Shropshire
 England
 T 01743 446666
 F 01743 442448
 enquiries@hoistquip.co.uk
 www.hoistquip.co.uk

Yale[®]

**Technical
 data**



	Capacity kg	Number of chain falls	Chain dimensions d x t in mm	Chain length for 1,5 m lift (standard) m	Lift with one full lever turn mm	Handle pull at WLL daN	Weight with std. lift kg
PUL-LIFT D85	750	1	6 x 18,5	1,7	111	38	8,2
	1500	1	9 x 27	1,8	45	31	16,3
	3000	1	11 x 31	1,8	33	40	19,6
	6000	2	11 x 31	3,6	17	42	32,9
	10000	3	11 x 31	5,5	11	37	60
PUL-LIFT C85	750	1	5/8" x 3/8"	1,7	115	38	8,7
	1500	1	1" x 1/2"	1,8	45	31	17
	3000	1	1 1/4" x 5/8"	1,8	36	40	22,2
	6000	2	1 1/4" x 5/8"	3,5	18	44	38
	10000	3	1 1/4" x 5/8"	5,4	12	44	67
PUL-LIFT D95	1500	1	6,2 x 18,5	1,8	35	27	9,9
	3000	1	9 x 27,2	1,8	38	49	16,5
Model AL	750	1	6,3 x 19,1	1,7	30	16	6,4
	1000	1	6,3 x 19,1	1,7	30	22	6,6
	1500	1	7,1 x 21,2	1,8	16	18	10
	3000	1	10 x 30,2	1,8	14	28	18
Model PT	750	1	5,6 x 17,1	1,7	24	21	5,7
	1500	1	7,1 x 21,2	1,8	23	25	9,3
	3000	1	9 x 27,2	1,8	16	35	14,9
	6000	2	9 x 27,2	3,6	8	38	28,5
Model AS	250	1	4 x 12	1,8	80	25	2,2

**Yale hoists and trolleys are
 not designed for passenger elevation
 applications and must not be used
 for this purpose!**