



Model	Capacity	Number of chain falls	Chain dimensions d x t in mm	Chain length for 3 m lift (std. lift) m	Hand chain overhaul for 1 m lift m	Lift per 1 m hand chain overhaul mm	Pull on hand chain at WLL daN	Net weight at std. lift kg
	kg							
<b>VS 0,5/1</b>	500	1	6 x 18	3,2	28	35	26	9
<b>VS 1/1</b>	1000	1	6 x 18	3,3	42	23	36	11,2
<b>VS 2/1</b>	2000	1	8 x 24	3,4	54	18	54	18
<b>VS 2/2</b>	2000	2	6 x 18	6,3	84	12	37	15,3
<b>VS 3/1</b>	3000	1	10 x 30	3,5	83	12	52	28
<b>VS 3/2</b>	3000	2	8 x 24	6,6	108	9	41	24,7
<b>VS 5/2</b>	5000	2	10 x 30	6,6	165	6	44	38,7
<b>VS 8/4</b>	8000	4	10 x 30	13,5	329	3	38	69,2
<b>VS 10/4</b>	10000	4	10 x 30	13,5	329	3	46	69,2
<b>VS 15/8</b>	15000	8	10 x 30	27,8	659	1	2 x 35	157,4
<b>VS 20/8</b>	20000	8	10 x 30	27,8	659	1	2 x 46	157,4

Model	Capacity kg	Size	Beam flange width b mm	Flange width t max. mm	Min. radius curve m	Net weight in kg for 3 m lift with locking device			
						VSTP	VSTG	VSTP	VSTG
<b>VSTP/G</b>	500	A	50 - 180	19	0,90	17,4	19,4	23,9	25,9
<b>VSTP/G</b>	500	B	180 - 300	19	0,90	18,8	20,8	25,3	27,3
<b>VSTP/G</b>	1000	A	58 - 180	19	0,90	22,6	28,3	30,6	36,3
<b>VSTP/G</b>	1000	B	180 - 300	19	0,90	24,8	30,5	32,8	38,5
<b>VSTP/G</b>	2000	A	58 - 180	19	1,15	33,8	38,0	41,8	46,0
<b>VSTP/G</b>	2000	B	180 - 300	19	1,15	37,5	41,7	45,5	49,7
<b>VSTP/G</b>	3000	A	74 - 180	27	1,40	66,0	69,0	75,2	78,2
<b>VSTP/G</b>	3000	B	180 - 300	27	1,40	68,0	71,0	77,2	80,2
<b>VSTP/G</b>	5000	A	98 - 180	27	1,80	100,3	106,5	110,8	117,0
<b>VSTP/G</b>	5000	B	180 - 300	27	1,80	103,0	109,2	113,5	119,7
<b>VSTG</b>	10000	B	125 - 310	40	1,80	-	175,0	-	-